







TUBO BRITOFLEX DIN - EN 854 3TE
2 TRECCE TESSILI - NO SKIVE

Sottostrato: gomma sintetica resistente agli olii
Rinforzo: due trecce in fibra tessile
Copertura: gomma sintetica resistente all'abrasione, agli olii e agli agenti atmosferici



Codice									
	Ø Interno tubo				Ø est. tubo	R min	PN	PS	Peso
	Inch	mm	SIZE	DN	mm	mm	bar	bar	g/m
3TE-03	3/16	4,6-5,4	3	5	12,0-13,6	40	160	640	120
3TE-04	1/4	6,2-7,0	4	6	13,6-15,2	45	145	580	150
3TE-05	5/16	7,7-8,5	5	8	16,1-17,7	55	130	520	210
3TE-06	3/8	9,3-10,1	6	10	17,7-19,3	70	110	440	240
3TE-08	1/2	12,3-13,5	8	12	20,7-22,7	85	93	372	290
3TE-10	5/8	15,5-16,7	10	16	24,9-26,9	105	80	320	400
3TE-12	3/4	18,6-19,8	12	19	28,0-30,0	130	70	280	470
3TE-16	1	25,0-26,4	16	25	34,4-37,4	150	55	220	630
3TE-20	1.1/4	31,4-33,0	20	32	40,8-43,8	190	45	180	770
3TE-24	1.1/2	37,1-39,1	24	38	47,6-51,6	240	40	160	970
3TE-32	2	49,8-51,8	32	51	60,3-64,3	300	33	132	1240